Model: C900 D5 Frequency: 50 Fuel Type: Diesel

# » Generator set data sheet 900 kVA Standby



## Our energy working for you.™

	Stand	Standby			Prime	Prime		
Fuel consumption	kW (k	kW (kVA)			kW (kVA)			
Ratings	720 (9	00)			656 (82	20)		
Load	1/4	1/2	3/4	Full	1/4	1/2	3/4	Full
US gph	13.1	24.2	35.4	47.0	12.2	22.5	32.0	42.5
L/hr	50	92	134	178	46	85	121	161

Engine	Standby rating	Prime rating
Engine manufacturer	Cummins	-
Engine model	QSK23G3	
Configuration	In-line 6 Cylinder Diese	el
Aspiration	Turbocharged and Afte	ercooled
Gross engine power output, kWm	768	701
BMEP at set rated load, kPa	2675	2441
Bore, mm	170	
Stroke, mm	170	
Rated speed, rpm	1500	
Piston speed, m/s	8.6	
Compression ratio	16:1	
Lube oil capacity, L	95	
Overspeed limit, rpm	1800 ±50	
Regenerative power, kWm	72	
Governor type	Electronic	
Starting voltage	24 Volts DC	
Fuel flow		
Maximum fuel flow, L/hr	662	
Maximum fuel inlet restriction, mm Hg	203	
Maximum fuel inlet temperature (°C)	60	
Air		
Combustion air, m <sup>3</sup> /min	53.3	48.7
Maximum air cleaner restriction, mm H <sub>2</sub> O	635	

Exhaust	Standby rating	Prime rating
Exhaust gas flow at set rated load, m <sup>3</sup> /min	147.8	135.5
Exhaust gas temperature, °C	543	532
Maximum exhaust back pressure, mmHg	76.2	

## Standard set-mounted radiator cooling

	•		
Ambient design, °C	40		
Fan load, KW <sub>m</sub>	15		
Coolant capacity (with radiator), L	95.5		
Cooling system air flow, m³/min @ 12.7mmH <sub>2</sub> O	882		
Total heat rejection, BTU/min	20965	19196	
Maximum cooling air flow static restriction mmH <sub>2</sub> O	12.7		


Weights*	Open	Enclosed
Unit dry weight kgs	6700	N.A.
Unit wet weight kgs	7023	N.A.


<sup>\*</sup> Weights represent a set with standard features. See outline drawing for weights of other configurations

Dimensions	Length "A"	Width "B"	Height "C"
Standard open set dimensions, mm	4593	1502	2086
Enclosed set standard dimensions, mm	20' container	-	-

### **Genset outline**


#### Open set





## **Enclosed set**





Outlines are for illustrative purposes only. Please refer to the genset outline drawing for an exact representation of this model.

## Our energy working for you. TM

#### www.cumminspower.com



#### **Alternator data**

Feature code	Connection <sup>1</sup>	Temp rise	Duty <sup>2</sup>	Alternator	Voltage
-	Wye, 3 Phase	150/125	S/P	НС6Н	380-415V

## **Ratings definitions**

Standby:	Limited Time Running:	Prime (unlimited running time):	Base Load (Continuous):
Applicable for supplying power to varying electrical load for the duration of power interruption of a reliable utility source. Emergency Standby Power (ESP) is in accordance with ISO 8528. Fuel Stop power in accordance with ISO 3046, AS 2789, DIN 6271 and BS 5514.	Applicable for supplying power to a constant electrical load for limited hours. Limited Time Running Power is in accordance with ISO 8528.	Applicable for supplying power to varying electrical load for unlimited hours. Prime Power is in accordance with ISO 8528. Ten percent overload capability is available in accordance with	Applicable for supplying power continuously to a constant

#### Notes:

- 1. Limited single phase capability is available from some three phase rated configurations. To obtain single phase rating, multiply the three phase kW rating by the single phase factor. All single phase ratings are at unity power factor.
- 2. Standby (S) and Prime (P) ratings.

## Formulas for calculating full load currents:

Three phase output Single phase output

 kW x 1000
 kW x 1000

 Voltage x 1.732 x 0.8
 Voltage

See your distributor for more information.

**Cummins Power Generation** 

**Asia Pacific** 

10 Toh Guan Road #07-01 TT International Tradepark Tel: (65) 6417 2388

Fax: (65) 6417 2399

E-Mail: cpg.apmktg@cummins.com

Our energy working for you.<sup>TM</sup>

