Model: C1675 D5A

Frequency: 50 Fuel Type: Diesel

# » Generator set data sheet 1675 kVA Standby



Prime

94.9

Our energy working for you.™

Air

Combustion air, m<sup>3</sup>/min

Maximum air cleaner restriction, mm H<sub>2</sub>O

uel consumption kw (kvA)			i i i i i i				
kW (kVA)		kW (kVA)					
1340 (1675)		1200 (1500)					
	3/4	Full	1/4	1/2	3/4	Full	
. 1	N.A.	91.1	23.2	44.1	62.9	81.6	
. 1	N.A.	345	88	167	238	309	
Standby rating			Prime rating				
(	Cummi	ns	<u> </u>				
ŀ	KTA50	GS8					
4	4-Cycle	e; 60° Vee	; 16-Cylin	16-Cylinder Diesel			
-	Turbo (	Charged a	nd Low To	nd Low Temperature Aftercooled			
•	1429			1287			
			2275 2062				
159			159				
•	159						
ŕ	1500						
7	7.9						
•	14.9:1						
ŕ	178						
	1800 ±	50					
ľ	116						
	Electronic						
24			24 Volts DC				
Ę	570						
203							
2	203						
		. N.A N.A Standt Cummi KTA50 4-Cycle Turbo ( 1429 2275 159 159 1500 7.9 14.9:1 178 1800 ± 116 Electro	. N.A. 91.1 . N.A. 345  Standby rating Cummins KTA50GS8 4-Cycle; 60° Vee Turbo Charged a 1429 2275 159 159 1500 7.9 14.9:1 178 1800 ±50 116 Electronic 24 Volts DC	1200 (cm   1200 (cm	1200 (1500)   1200 (1500)	1200 (1500)   1/4   1/2   3/4     1/2   3/4     1/2   3/4     1/2   3/4     1/2   3/4     1/2   3/4     1/2   3/4     1/2   3/4     1/2   3/4     1/2   3/4     1/2   3/4     1/2   3/4     1/2   3/4     1/2   3/4     1/2   1/2     1/2	

99.2

635

Standby

Exhaust	Standby rating	Prime rating
Exhaust gas flow at set rated load, m <sup>3</sup> /min	260.8	242.3
Exhaust gas temperature, °C	510	499
Maximum exhaust back pressure, mmHg	51	

## Standard set-mounted radiator cooling

	9		
Ambient design, °C	40		
Fan load, KW <sub>m</sub>	30		
Coolant capacity (with radiator), L	315		
Cooling system air flow, m <sup>3</sup> /min @ 12.7mmH <sub>2</sub> O	1560		
Total heat rejection, BTU/min	52430	44750	
Maximum cooling air flow static restriction mmH <sub>2</sub> O	12.7	•	


Weights*	Open	Enclosed
Unit dry weight kgs	11300	N.A.
Unit wet weight kgs	12000	N.A.


<sup>\*</sup> Weights represent a set with standard features. See outline drawing for weights of other configurations

Dimensions	Length "A"	Width "B"	Height "C"
Standard open set dimensions, mm	5637	2250	2250
Enclosed set standard dimensions, mm	40' container	-	-


## **Genset outline**


#### Open set





## **Enclosed set**





Outlines are for illustrative purposes only. Please refer to the genset outline drawing for an exact representation of this model.

## Our energy working for you.<sup>TM</sup>

#### www.cumminspower.com



### **Alternator data**

Feature code	Connection <sup>1</sup>	Temp rise	Duty <sup>2</sup>	Alternator	Voltage
-	Wye, 3 Phase	150/125	S/P	P7D	380-415V

## **Ratings definitions**

Standby:	Limited Time Running:	Prime (unlimited running time):	Base Load (Continuous):
Applicable for supplying power to varying electrical load for the duration of power interruption of a reliable utility source. Emergency Standby Power (ESP) is in accordance with ISO 8528. Fuel Stop power in accordance with ISO 3046, AS 2789, DIN 6271 and BS 5514.	Applicable for supplying power to a constant electrical load for limited hours. Limited Time Running Power is in accordance with ISO 8528.	to varying electrical load for unlimited hours. Prime Power is in accordance with ISO 8528. Ten percent overload capability is available in accordance with	Applicable for supplying power continuously to a constant electrical load for unlimited hours. Continuous power in accordance with ISO 8528, ISO 3046, AS 2789, DIN 6271 and BS 5514.

#### Notes:

- 1. Limited single phase capability is available from some three phase rated configurations. To obtain single phase rating, multiply the three phase kW rating by the single phase factor. All single phase ratings are at unity power factor.
- 2. Standby (S) and Prime (P) ratings.

# Formulas for calculating full load currents:

Three phase output Single phase output

 kW x 1000
 kW x 1000

 Voltage x 1.732 x 0.8
 Voltage

See your distributor for more information.

**Cummins Power Generation** 

Asia Pacific

10 Toh Guan Road #07-01 TT International Tradepark Tel: (65) 6417 2388

Fax: (65) 6417 2399

E-Mail: cpg.apmktg@cummins.com

Our energy working for you. TM

