Model: C80 D5 Frequency: 50 Fuel Type: Diesel

» Generator set data sheet 80 kVA Standby



Our energy working for you.™

Maximum air cleaner restriction, mm H₂O

	Standby		Prime kW (kVA)					
Fuel consumption	kW (kVA) 64 (80)							
Ratings					58 (73)			
Load	1/4	1/2	3/4	Full	1/4	1/2	3/4	Full
US gph	1.3	2.9	4.2	5.5	1.3	2.4	3.7	4.8
L/hr	5	11	16	21	5	9	14	18
Engine		Standb	Standby rating Prime rating					
Engine manufacturer			Cummi	Cummins				
Engine model			4BTA3.	4BTA3.9G3				
Configuration			4 Cycle; In-line; 4 Cylinder Diesel					
Aspiration			Turbo (Turbo Charged and Aftercooled				
Gross engine power output, kWm			81		73			
BMEP at set rated load, kPa			1652	52 1485				
Bore, mm	ore, mm		102					
Stroke, mm		120						
Rated speed, rpm		1500						
Piston speed, m/s			6					
Compression ratio		16.5:1						
Lube oil capacity, L			9.5					
Overspeed limit, rpm			1800 ±50					
Regenerative power, kWm			8.2					
Governor type			Electronic					
Starting voltage			12 Volts DC					
Fuel flow			Ī					
Maximum fuel flow, L/hr		30						
Maximum fuel inlet restriction, mm Hg		102						
Maximum fuel inlet temperature (°C)		60						
Air								
Combustion air, m ³ /min			5.1			4.8		
Mandanasa ala ala anana antalatika anana								

635

Standby rating	Prime rating
13.8	12.5
567	563
76	
	13.8

Standard set-mounted radiator cooling

•		
Ambient design, °C	50	
Fan load, KW _m	2	
Coolant capacity (with radiator), L	21	
Cooling system air flow, m ³ /min @ 12.7mmH ₂ O	system air flow, m ³ /min @ 12.7mmH ₂ O 120	
Total heat rejection, BTU/min	2423	2141
Maximum cooling air flow static restriction mmH ₂ O	12.7	


Weights*	Open	Enclosed
Unit dry weight kgs	1120	1725
Unit wet weight kgs	1335	1935


^{*} Weights represent a set with standard features. See outline drawing for weights of other configurations

Dimensions	Length "A"	Width "B"	Height "C"
Standard open set dimensions, mm	1920	1050	1438
Enclosed set standard dimensions, mm	2710	1060	1835


Genset outline


Open set





Enclosed set






Outlines are for illustrative purposes only. Please refer to the genset outline drawing for an exact representation of this model.

Our energy working for you. TM

www.cumminspower.com





Alternator data

Feature code	Connection ¹	Temp rise degrees C	Duty ²	Alternator	Voltage
-	Wye, 3 Phase	163/125C	S/P	UC224F	380-415V

Ratings definitions

Standby:	Limited Time Running:	Prime (unlimited running time):	Base Load (Continuous):
Applicable for supplying power to varying electrical load for the duration of power interruption of a reliable utility source. Emergency Standby Power (ESP) is in accordance with ISO 8528. Fuel Stop power in accordance with ISO 3046, AS 2789, DIN 6271 and BS 5514.	to a constant electrical load for limited hours. Limited	unlimited hours. Prime Power is in accordance with ISO 8528. Ten percent overload capability	Applicable for supplying power continuously to a constant electrical load for unlimited hours. Continuous power in accordance with ISO 8528, ISO 3046, AS 2789, DIN 6271 and BS 5514.

Notes:

- Limited single phase capability is available from some three phase rated configurations. To obtain single phase rating, multiply the three phase kW rating by the single phase factor. All single phase ratings are at unity power factor.
- 2. Standby (S) and Prime (P) ratings.

Formulas for calculating full load currents:

Three phase output Single phase output

 kW x 1000
 kW x 1000

 Voltage x 1.732 x 0.8
 Voltage

See your distributor for more information.

Cummins Power Generation

Asia Pacific

10 Toh Guan Road #07-01 TT International Tradepark Tel: (65) 6417 2388 Fax: (65) 6417 2399

E-Mail: cpg.apmktg@cummins.com

Our energy working for you. TM

www.cumminspower.com

