# HD 5/17 C



Cold-water pressure washer for daily commercial use. With its compact dimensions, robust construction and greatest possible manoeuvrability, this unit is a credit to the compact class.

- Trigger gun Easy Press
- Trigger gun with Softgrip insert
- High-pressure hose 10 m
- Spray lance 850 mm
- Triple nozzle (0°/25°/40°).
- Anti-twist system
- Pressure cut-off

Order number: 1.214-120.0



| Supply voltage Ph/V/Hz       | 1/230/50    |
|------------------------------|-------------|
| Flow rate (I/h)              | 250-500     |
| Operating pressure (bar/MPa) | 30-170/3-17 |
| Max. pressure (bar/MPa)      | 215/21.5    |
| Max. inlet temperature (°C)  | 60          |
| Power rating (kW)            | 3.2         |
| Weight (kg)                  | 23          |
| Measures (L x W x H) (mm)    | 360x375x925 |

## **Adapter**

### Adapter M22 - Swivel

M22 x 1,5female and swivel connection. For extension of high-pressure hoses with AVS connection or for usage of the telescopic lance with a high-pressure hose with AVS connection.



Order number 4.424-004.0

## **Angular spray lance**

### WC and gutter lance

Stainless steel lance WC and gutter with nozzle insert. Specially shaped for effective and hygienic cleaning of gutters and toilets.



Order number 4.760-073.0

## Automatic, self-winding hose reels

## Hose reel, automatic, 20 m, painted

Automatic hose reel of durable plastic. Painted steel bracket. Suitable for 20 m high-pressure hose.



Order number 2.639-919.0

#### Swivel holder

Swivel holder for automatic hose reel wall mounting. For maximum action radius and flexibility of high-pressure hose. Rotatable 120°. Galvanised steel.

Order number 2.639-931.0



## Hose reel, automatic, 20 m, stainless steel

Automatic stainless steel hose reel. With swivel holder. Suitable for 20 m high-pressure hose.

Order number 6.391-421.0



#### ABS hose reel stainless steel

High-grade, automatic steel hose reel. Especially suitable for use in the food industry. The material and finish provide for a corrossion-resistant, watertight capsuled sprong drive. Connection for HP hoses with nipple.



Order number 2.641-866.0

## ABS wall fastening stainless steel

Swivelling wall bracket made of high-grade steel (for 2.641-866). This makes maximum flexibility and convenience possible when working with the HP hose.

Order number 2.641-867.0



## Automatic, self-winding hose reels

## Add-on kit hose reel

Automatic hose reel for 20 m high-pressure hose. The console consists of stainless steel, the drum is made from plastic.

Order number 6.392-965.0



## Add-on kit hose reel plastics

Automatic hose reel for 20 m high-pressure hose. The console is made from powder-coated steel, the drum is made from plastic.

Order number 6.392-975.0



#### **Backflow check valve**

#### **Backflow preventer**

To prevent detergent getting into the drinking water cycle in case of inlet at low-pressure. - hot water resistant up to 80 °C - tested according to IEC 60335-2-79 - integrated leakage protection

Order number 2.641-374.0



#### Boron carbide nozzle

## Boron carbide nozzle, for machines as of 1000 l/h

In addition to nozzle packs. Very wear-resistant nozzle with boron carbide chuck for continuous-duty operation.

Order number 6.415-084.0



## Coupling

#### Hose connector

Brass double connector for connecting and extending high-pressure hoses. With rubber protection. Connector: 2x M 22 x 1.5 m.



Order number 4.403-002.0

## **Cup foam lance**

#### Cup foam lance

Short, handy foam lance with adjustable spray angle with 1 litre detergent tank. Ideal for cleaning cars due to its compact design.

Order number 6.394-668.0



## **Cup foam lance**

#### Tank 1L

Order number 6.414-954.0



## Dirt blaster, large

## Dirt blaster - without changeover function

The dirt blaster with rotating pencil jet offers 10 times better cleaning performance. Ceramic nozzle and bearing ring for a long service life. Further data: Max. 300 bar, 30 MPa, 85°C.

Order number 4.763-931.0



## Dirt Blaster, small

#### Dirt blaster

The dirt blaster with rotating pencil jet offers 10 times better cleaning performance. Ceramic nozzle and bearing ring for a long service life. Further data: Max. 180 bar, 18 MPa, 60°C.

Order number 4.767-041.0



#### **Double lance**

#### Double lance 960 mm

960 mm double lance for variable pressure adjustment on handle at full water flow rate. Suitable for agricultural use (e.g. stable cleaning).

Order number 6.394-665.0



## Easy Press high-pressure gun with holding power reduction (Kärcher patent)

## Easy press high-pressure trigger gun with softgrip

Easy press high-pressure trigger gun with softgrip. For high-pressure hoses DN 6 and DN 8 with 11 mm swivel diameter.

Order number 4.775-463.0



#### Fine-mesh water filter

### Fine-mesh water filter with adapter

Fine-mesh water filter, 125  $\mu$ m, max. temperature 50°C. Protects the high-pressure cleaner from dirt particles contained in the water. Water flow rate up to 1200 l/h. Connection 3/4", with adapter, 1".

Order number 4.730-102.0



# Flexible spray lance

## Flexible lance 1050 mm

1050 mm flexible lance with variable bend from 20° to 140°, ideal for cleaning difficult to reach areas, e.g. gutters.

Order number 6.394-654.0



#### Floor and hard surface cleaner

## FR Xpert hard surface cleaner

A rotating nozzle beam with Kärcher Power nozzles has an area coverage up to 10 times larger than conventional methods. Plastic cover for good manoeuvrability. Nozzle kit included in delivery. Max. 180 bar / 600 l/h / 60 °C

Order number 2.641-686.0



# Foam nozzle mounting kit

#### Foam nozzle kit

Foaming agent kit. The foam nozzle is ideal for use in sanitary areas and the food industry and wherever long application times are necessary.



Order number 2.637-926.0

## Food industry version

# High-pressure hose 15 m ID 6, AVS trigger gun connector 11 mm, suitable for food industry, grey

15 m high-pressure hose (DN 6) with patented (rotating) AVS trigger gun connector. Non-discolouring outer layer for use in the food industry. DN 6/155°C/250 bar.

Order number 6.391-654.0



## Food industry version with unions on both sides

# High-pressure hose, 10 m ID 8, suitable for food industry, extension piece

10 m high-pressure hose (DN 8) with patented (rotating) AVS trigger gun connector. Non-discolouring outer layer for use in the food industry. M  $22 \times 1.5$  with anti-kink sleeve.



Order number 6.389-479.0

# High-pressure hose, 20 m ID 8, suitable for food industry, extension piece

20 m high-pressure hose (DN 8) with swivel coupling. Non-discolouring outer layer for use in the food industry. Connectors at both ends, M 22 x 1.5, with kink protection. NW 8/155°C/250 bar.



Order number 6.389-581.0

## **Geka coupling**


With hose nozzle, R 1/2" with hose liner

Order number 6.388-461.0



With hose nozzle, R 3/4" with hose liner

Order number 6.388-455.0



With female thread, R 3/4" with female thread

Order number 6.388-473.0



#### **Gutter cleaner**

## **Gutter cleaning lance**

The lance is suited for cleaning of gutter systems. Because of the shape of the lance and the special nozzle the gutter can be cleaned without removing the cover plates.



Order number 2.642-305.0

### Hard surface cleaner FR 30

### FR 30 hard surface cleaner

A rotating nozzle beam with Kärcher Power nozzles has an area coverage up to 10 times larger than conventional methods. Ceramic bearings, plastic cover for good manoeuvrability. Machine specific nozzle kit has to be ordered separately. Max. 180 bar / 850 l/h / 60  $^{\circ}$ C

Order number 2.641-065.0



### Hard surface cleaner FR 30 ME

## FR 30 ME surface cleaner

Hot water resistant stainless steel surface cleaner with double ceramic bearings, non-marking swivel castors and suction hose connection. Ideal for indoor cleaning, e.g. food industry.



Order number 2.640-355.0

## Hard surface cleaner FRV 30

#### **FRV 30**

With the integrated, automatic suction of the waster water the FRV 30 allows more efficient surface cleaning for indoor and outdoor usage. The inconvenient flushing of the surface after cleaning is not necessary anymore because the waster water can be drained off well-directed through the included 5m suction hose. Non-marking wheels and ceramic bearings are further quality features.



## Hard surface cleaner FRV 30

Machine specific nozzle kit has to be ordered separately. Max. 250 bar / 1000 l/h /  $60^{\circ}$ C.

Order number 2.642-169.0

### Add-on kit rubber lip

For smooth floors indoors. The squeegee increases the suction performance of the FRV 30 and minimises the amount of water remaining. This means the floor is dry in just a few minutes.

Order number 2.642-910.0

# **HP** detergent injector

### Detergent injector for high pressure

Cleaning agent dosage at high pressure 3 - 5 %

Order number 3.637-170.0



#### Inaktiv

## Spray lance, 2,050 mm, swivelling, ergonomical

Spray lance, 2,050 mm, swivelling, ergonomical

Order number 4.760-366.0



## Longlife 400

## High pressure hose DN 6, 10 m, Longlife

With patented AVS connection in the trigger gun (pivot-mounted).

Order number 6.391-882.0



## High-pressure hose packaged

Order number 6.391-351.0



## Longlife 400 with unions on both sides

## High-pressure hose 1.5 m, ID 8, including connectors

1.5 m high-pressure hose (DN 8, M 22 x 1.5) with kink protection and connectors at both ends. For connecting to hose reels with appropriate connector (M  $22 \times 1.5$ ).



Order number 6.390-178.0

# High-pressure hose Longlife 400, 10 m, ID 8, including rotary coupling

10 m high-pressure hose Longlife 400 (DN 8) with rotary coupling, two layer high-strength steel wire reinforced. Connectors at both ends. M 22 x 1.5, with kink protection.



Order number 6.388-083.0

# High-pressure hose Longlife 400, 10 m, DN 8, extension

without rotary coupling, 2 x M 22 x 1.5

Order number 6.390-026.0



# Longlife 400 with unions on both sides

# High-pressure hose Longlife 400, 20 m, ID 8, extension

with rotary coupling, 2 x M 22 x 1.5


Order number 6.390-027.0



## High pressure hose ID 6, 10 m, drehbar,I

With rotary coupling, 2 x M 22 x 1,5

Order number 6.391-883.0



Order number 6.391-354.0



With rotary coupling, 2 x M 22 x 1.5

Order number 6.389-709.0



# High-pressure hose Longlife 400, 30 m ID 8, including rotary coupling

With rotary coupling, 2 x M 22 x 1.5

Order number 6.390-294.0

# Longlife food industry version

# HIgh-pressure hose Longlife 400, 15 m, ID 6, AVS trigger gun connection

Longlife HP hose for use in the food industry. Außendecke## animal-grease-resistant, non-colour-bleeding material. With patented AVS connection in the pistol (pivot mounted)

Order number 6.391-888.0



## Longlife food industry version with unions on both sides

## High pressure hose food ID 8 / 10 m

Longlife HP hose for use in the food industry. Außendecke## animal-grease-resistant, non-colour-bleeding material. With rotary coupling,  $2 \times M \times 22 \times 1,5$ 

Order number 6.391-864.0



# High-pressure hose food industry 400 bar, 20 m, ID 8, including rotary coupling

Longlife HP hose for use in the food industry. Außendecke## animal-grease-resistant, non-colour-bleeding material. With rotary coupling, 2 x M 22 x 1,5

Order number 6.391-887.0



## Machine-specific nozzle kit for FR

# Nozzle kit for surface cleaners (type-specific) 450 - 500 l/h

Nozzle kit includes power nozzles and unions. For Kärcher surface cleaners (450 to 500 l/h).

Order number 2.640-482.0



## Machine-specific nozzle kit with order no. 3.637-170

#### Machine-specific nozzle kit with order no. 3.637-170.0 HD 500-700 l/h

For HD 500 - 700 l/h. Consists of nozzle insert + HP power nozzle + union

Order number 4.769-045.0



## Nozzle pack for wet blasting attachment

## Nozzle kit for wet blasting attachment 035

Nozzle kit with wet blasting nozzle and nozzle insert (type specific). For optimal Kärcher wet blasting attachment performance. Only in combination with wet blasting attachment 4.762-010/-022.

Order number 2.638-526.0



#### **Nozzle union**

#### **Nozzle connector**

For protecting and connecting Kärcher power nozzles to spray lances (M 18 x 1.5 IG).

Order number 5.401-210.0



## Pipe cleaning hose, ID 6

## Pipe cleaning hose

20 m flexible high-pressure hose (DN 6) for cleaning pipes (threaded connection for R 1/8 nozzle).

Order number 6.390-028.0



## Pipe cleaning hose, DN 6, 30 m

30 m flexible high-pressure hose (DN 6) for cleaning pipes (threaded connection for R 1/8 nozzle).



Order number 6.390-029.0

### Pipe cleaning nozzle

## Rotating pipe cleaning nozzle

Rotating pipe cleaning nozzle with internal thread and four rotating jets for environmentally-friendly cleaning of blocked drains and pipes.



Order number 6.415-428.0

# Pipe cleaning nozzle

The forward-tilted rotating pencil jet removes the most stubborn dirt. The three backwards-tilted jets ensure the necessary forward movement, as well as convenient handling.

Order number 6.415-944.0

The forward-tilted rotating pencil jet removes the most stubborn dirt. The three backwards-tilted jets ensure the necessary forward movement, as well as convenient handling.

Order number 6.415-946.0

The forward-tilted rotating pencil jet removes the most stubborn dirt. The three backwards-tilted jets ensure the necessary forward movement, as well as convenient handling.

Order number 6.415-948.0

## Power nozzle spray angle 25°

PCH / Power Nozzle 25250

Order number 5.765-078.0

# Push-on washing brush

#### Push-on wash brush

Push-on wash brush for double/triple nozzle. Simply push on to nozzle.

Order number 4.762-328.0



#### Push-on wash brush, M 18 x 1.5

Push-on wash brush for universal use. Simply push on to lance. Connector: M 18 x 1.6.



## Push-on washing brush

With clamp for mounting directly to units' double or triple nozzle. Fits on new double and triple nozzles.

Order number 4.762-497.0



#### **Quick connect**

## Quick coupling

For quick change of different spray lances and accessories. Optimum adaption to Kärcher accessories, especially for connection between trigger gun and spray lance. With M22 x 1,5 female.



Order number 6.401-458.0

## **Quick connect**

#### Plug nipple

Hardened stainless steel nipple for quick coupling 6.401-458. With M22 x 1,5 male.



Order number 6.401-459.0

#### Rollover nozzle holder

#### Rollover nozzle holder

Rollover nozzle holder for contactless changeover from pencil jet to fan jet as well as low-pressure detergent injection via knurled nut. Without nozzle insert. (Additional type-specific power nozzle).



Order number 4.764-012.0

# **Rotary coupling**

## Rotary coupling

Reliably prevents high-pressure hose twisting. Connection M 22 x 1.5 m. protector



Order number 4.401-076.0

#### Rotary coupling

Kärcher rotary coupling prevents twisting and kinking of high-pressure hoses for ease of use. Connector M 22 x 1.5 m. With grip protection.



Order number 4.401-091.0

# **Rotating spray lances**

### Lance 850 mm, rotatable, ergonomic

850 mm stainless steel lance (manual coupling) with ergonomic handle for ease of use and protection. Rotatable 360° under pressure.



Order number 4.760-663.0

## Rotatable lance, 600 mm, ergonomic

600~mm stainless steel lance (manual coupling) with ergonomic handle for ease of use and protection. Rotatable  $360^\circ$  under pressure.



Order number 4.760-664.0

#### 1050 mm lance, rotatable, ergonomic

1050 mm stainless steel lance (manual coupling) with ergonomic handle for ease of use and protection. Rotatable 360° under pressure.





#### Lance 1550 mm, rotatable, ergonomic

1550 mm stainless steel lance (manual coupling) with ergonomic handle for ease of use and protection. Rotatable 360° under pressure.

Order number 4.760-661.0



# **Rotating spray lances**

## Lance 2050 mm, rotatable, ergonomic

2050 mm stainless steel lance (manual coupling) with ergonomic handle for ease of use and protection. Rotatable 360° under pressure.

Order number 4.760-662.0



## Rotating washing brush

# Rotating washing brush for <#38;#60; 800 l/h high-pressure cleaners

The rotating wash brush driven by the water jet is suitable for > 800 l/h highpressure cleaners; gently and effectively removes fine dust and grime from all surfaces.



Order number 4.762-284.0

# Rotating washing brush for <#38;#60; 800 l/h high-pressure cleaners

The rotating wash brush driven by the water jet is suitable for > 800 l/h high-pressure cleaners; gently and effectively removes fine dust and grime from all surfaces.



Order number 4.762-288.0

# Spacer (including nozzle union)

## Spacer (incl.nozzle union)

Guarantees constant safety clearance, e.g. for tyres and bodywork. Helps prevent damage to sensitive surfaces. Mounts directly to lance.



Order number 5.394-294.0

## Special hoses

High-pressure hose 1.5 m, ID 8, including connectors, outlet bend Order number 6.388-886.0



## **Spray lance**

### Lance 250 mm, non-rotatable

250 mm stainless steel lance. With manual coupling. Non-rotatable.

Order number 4.760-667.0



## **Spray lances**

#### **Anti-vibration lance**

The spring-loaded 360° loop handle significantly reduces the vibrations on the spray lance, reducing the physical burden on the user, e.g. when working with the dirt blaster.



Order number 6.415-951.0

#### standard

## High-pressure hose, 10 m DN 6, AVS trigger gun connector

10 m high-pressure hose (M 22 x 1.5) with kink protection. With patented rotating AVS trigger gun connector and manual coupling. Further data: DN 6/155°C/250 bar.

Order number 6.391-238.0



HD-Schlauch DN 6, 15m

Order number 6.391-394.0



High-pressure hose, 10 m, DN 6, 300 bar, AVS trigger gun connection

With patented AVS connection in the trigger gun (pivot-mounted) and hand screw union. M 22 x 1.5 with anti-kink protection. NW 6/155°C/300 bar

Order number 6.391-875.0



High-pressure hose, 10 m DN 8, 315 bar, extension

with union on both sides, M 22 x 1,5 with anti-kink protection. NW  $8/155^{\circ}$ C/315 bar

Order number 6.389-891.0



High-pressure hose, 15 m DN 8, 315 bar, including rotary coupling

With rotary coupling, 2 x M 22 x 1.5

Order number 6.390-010.0



High-pressure hose, 20 m DN 8, 315 bar, extension

With M 22x1.5 union at both ends and anti-kink protection ID 8/155°C/315 bar

Order number 6.390-031.0



High-pressure hose, 15 m DN 10, 220 bar, extension

15 m high-pressure hose M 22 x 1.5) with kink protection and threaded couplings at both ends. Further data: DN 10/155°C/220 bar.

Order number 6.390-023.0



## Standard with unions on both sides

# High-pressure hose packaged

Order number 6.391-342.0



## High-pressure hose, 30 m DN 8, including rotary coupling

With rotary coupling, 2 x M 22 x 1.5

Order number 6.390-293.0



## Starting current limiter

## Starting current limiter

Reduces starting current in single-phase supply and protects line fuse.

Order number 2.637-495.0



#### **Suction filter**

#### Suction filter with check valve

Brass suction filter suitable for ponds, storage tanks, etc. With check valve.

Order number 4.730-012.0



## Suction filter without non-return valve

Without non-return valve, brass

Order number 4.730-019.0



### Water filter

Order number 6.414-956.0



## **Telescopic spray lance**

## Telescopic jet pipe

Order number 6.394-690.0



Convenient strap for relief when working with the telescopic spray lance (6.394-690). The burden is optimally distributed on the body and longer periods of use are possible.

Order number 6.373-987.0



# **Trigger guns**

## High end high-pressure trigger gun

Order number 4.775-823.0



# **Triple nozzles**

## Triple nozzle 028

Triple nozzle with manual nozzle changeover. Convenient spray adjustment. For high-pressure cleaners with injector; low-pressure fan jet for detergent removal and application. Connector M 18x1.5.



Order number 4.767-144.0

## Water supply hose

## Water supply hose

NW 13 R1" / R 3/4", up to 30 °C

Order number 4.440-038.0



## Water supply hose

NW 19 R1" / R 3/4", up to 85 °C, for pick-up

Order number 4.440-207.0

