

## SPP 33 Inox

Regular and targeted watering is necessary to make your garden blossom. That is now child's play with Kärcher's new garden pumps and submersible pressure pumps. These high-performance pumps have enough pressure to run several sprinklers simultaneously. Water pressure is maintained over long distances so that you can make practical use of water from springs, wells, ponds or rain barrels. Installation and operation are really simple.

- Stainless steel pump body
- Comfortable carry handle
- Connecting hose 1"
- 3/4"
- 1/2"
- Simple definition of switching level .

**Order number: 1.645-400.0**



|                                       |             |
|---------------------------------------|-------------|
| Max. motor rating (W)                 | 850         |
| Max. flow rate (l/h)                  | 6200        |
| Delivery head/pressure, max. (mm/bar) | 33/3.3      |
| Max. depth of immersion (m)           | 9           |
| Pump travelling mechanism             | 3-stufig    |
| Diameter (mm)                         | 220         |
| Delivery temperature, max. (°C)       | 35          |
| Weight without accessories (kg)       | 7.4         |
| Measures (L x W x H) (mm)             | 220x220x400 |
| Connecting thread                     | G1 1/4      |
| Power cord                            | H07RN-F 10m |

## Adapters / connectors

### Pump adapter including <sup>5</sup>/<sub>8</sub> Check valve, large

Pump adapter with check valve for vacuum-resistant connection of suction hoses to pumps (e.g. garden pumps and high-pressure pumps for domestic use).

**Order number 6.997-418.0**



## Suction hoses

### Suction hose available in bulk

Vacuum-resistant spiral hose can be cut to length for connection to submersible, garden, submersible pressure pumps and high-pressure pumps.

**Order number 6.997-346.0**



### Suction hose available in bulk

Vacuum-resistant spiral hose can be cut to length for connection to submersible, garden, submersible pressure pumps and high-pressure pumps.

**Order number 6.997-347.0**

