


TCD 2013

for power generating sets

90 - 260 kW | 121 - 349 hp at 1500/1800 min⁻¹ | rpm

EU Stage IIIA / US EPA Tier 3

- Watercooled 4 or 6-cylinder inline engines with turbocharging and charge air cooling.
- The powerful DEUTZ Common Rail (DCR[®]) injection system and the electronic engine control (EMR 4) with intelligent link to the drive management ensure optimum engine performance at low fuel consumption.
- Easy, inexpensive installation due to minimum weight and small installation space.



- Air filter and cooling system are fully pre-assembled.

- Low noise emissions due to acoustically optimized components with very smooth running and high durability.
- Wet cylinder liners, long oil change intervals and easy changing of the engine fluids reduce the running costs and increase the availability of the machinery.
- Best cold starting performance even under extreme conditions.
- The TCD 2013 meets the requirements of the EU Stage IIIA and US EPA Tier 3.

Technical data

Engine type	TCD 2013 L4 2V	TCD 2013 L6 2V	TCD 2013 L6 4V
No. of cylinders	4	6	6
Bore/stroke	mm in	108/130 4.3/5.1	108/130 4.3/5.1
Displacement	l cu in	4.8 293	7.2 439
Weight with cooling system and air filter	kg lb	660 1455	945 2083
Governing standard ¹⁾	G2	G3	G3

50 Hz / 1500 min⁻¹

Power	TCD 2013 L4 2V	TCD 2013 L6 2V	TCD 2013 L6 4V
Continuous Power (COP) ²⁾	kW hp	90 121	136 182
Prime Power (PRP) ³⁾	kW hp	95 128	144 192
Limited Time Power (LTP) ⁴⁾	kW hp	100 135	151 202
Fan power consumption	kW hp	2.6 3	5.0 7
Typical Generator Output COP ⁵⁾	kVA	99	151
Typical Generator Output PRP ⁵⁾	kVA	104	159
Typical Generator Output LTP ⁵⁾	kVA	110	168

60 Hz / 1800 min⁻¹

Power output	TCD 2013 L4 2V	TCD 2013 L6 2V	TCD 2013 L6 4V
Continuous Power (COP) ²⁾	kW hp	103 138	156 209
Prime Power (PRP) ³⁾	kW hp	109 146	165 221
Limited Time Power (LTP) ⁴⁾	kW hp	114 153	174 233
Fan power consumption	kW hp	4.4 6	8.7 12
Typical Generator Output COP ⁵⁾	kWe	89	136
Typical Generator Output PRP ⁵⁾	kWe	94	144
Typical Generator Output LTP ⁵⁾	kWe	99	152

1) According to ISO 8528-5.

2) Continuous Power: No time limitation, plus 10% additional power for governing purpose only.

3) Prime Power: Average power output ≤ 80%, no time limitation, plus 5% additional power for governing purpose only.

4) Limited Time Running Power: For up to 500 h/year, thereof a maximum of 300 h/year continuous running.

5) In consideration of a generator efficiency level of 90 - 92 % and a power factor of 0.8.

50 Hz / 1500 min⁻¹

Fuel Consumption (PRP) ⁶⁾		TCD 2013 L4 2V	TCD 2013 L6 2V	TCD 2013 L6 4V
Fuel consmption 25% load	g/kWh lb/hph	318 0.52	260 0.43	253 0.42
Fuel consmption 50% load	g/kWh lb/hph	284 0.47	249 0.41	235 0.39
Fuel consmption 75% load	g/kWh lb/hph	270 0.44	236 0.39	225 0.37
Fuel consmption 100% load	g/kWh lb/hph	244 0.40	216 0.36	210 0.35
Heat balance & cooling system		TCD 2013 L4 2V	TCD 2013 L6 2V	TCD 2013 L6 4V
Heat dissipation (engine radiator) ²⁾	kW hp	50 67	74 99	133 178
Heat dissipation (CAC) ²⁾	kW hp	19 25	23 31	39 52
Heat dissipation (convection)	kW hp	9 12	14 19	23 31
Cooling air flow	m ³ /h cfm	6480 3814	11500 6769	15480 9111
Inlet & exhaust data		TCD 2013 L4 2V	TCD 2013 L6 2V	TCD 2013 L6 4V
max. intake depression	mbar psi	10 0.15	10 0.15	10 0.15
Combustion air volume	m ³ /h cfm	450 265	600 353	756 445
max. exhaust gas temperature	°C °F	530 986	485 905	515 959
Exhaust gas flow	m ³ /h cfm	1261 742	1587 934	2079 1224

60 Hz / 1800 min⁻¹


Fuel Consumption (PRP) ⁶⁾		TCD 2013 L4 2V	TCD 2013 L6 2V	TCD 2013 L6 4V
Fuel consmption 25% load	g/kWh lb/hph	318 0.52	288 0.47	255 0.42
Fuel consmption 50% load	g/kWh lb/hph	282 0.46	260 0.43	234 0.38
Fuel consmption 75% load	g/kWh lb/hph	263 0.43	243 0.40	245 0.40
Fuel consmption 100% load	g/kWh lb/hph	233 0.38	223 0.37	218 0.36
Heat balance & cooling system		TCD 2013 L4 2V	TCD 2013 L6 2V	TCD 2013 L6 4V
Heat dissipation (engine radiator) ⁷⁾	kW hp	57 76	73 98	141 189
Heat dissipation (CAC) ⁷⁾	kW hp	20 27	26 35	46 62
Heat dissipation (convection)	kW hp	10 13	16 21	24 32
Cooling air flow	m ³ /h cfm	7560 4450	13320 7840	18720 11018
Inlet & exhaust data		TCD 2013 L4 2V	TCD 2013 L6 2V	TCD 2013 L6 4V
max. intake depression	mbar psi	20 0.29	20 0.29	20 0.29
Combustion air volume	m ³ /h cfm	492 290	660 388	858 505
max. exhaust gas temperature	°C °F	540 1004	511 952	485 905
Exhaust gas flow	m ³ /h cfm	1396 822	1806 1063	2270 1336

6) Refers to diesel with a density of 0.835 kg/dm³ at 15°C | 6.96 lb/US gallon at 60°F.

7) The heat quantities are valid for the dimensioning of the cooling system.

The data on this data sheet are for information purposes only and are not binding values. The data in the quotation is definitive.

Dimensions



	A	B	C
TCD 2013 L4 2V	mm	1589	880
TCD 2013 L6 2V	mm	1909	879
TCD 2013 L6 4V	mm	1865	1046
			1247
			1263
			1322

Note: The engine dimensions and weights vary depending on the scope of delivery.

For more information please contact the DEUTZ AG Köln or the responsible sales partner.