

Stamford : ژنراتور

LOVOL-china : موتور دیزل

Standby		Prime		دیزل ژنراتور
KVA	KW	KVA	KW	
193	155	176	141	



موتور دیزل		
Manufacturer	LOVOL-china	تولید کننده
Type	1106TAG3	تیپ
Speed rpm	1500	سرعت
Number of cylinders	6	تعداد سیلندر ها
Compression ratio	17.0:1	ضریب تراکم
Cylinder arrangement	Vertical, in-line	آرایش سیلندر ها
Displacement , Liters	5.99 liters	جا به جایی
Bore × Stroke , mm	100mm×127mm	قطر سیلندر × کورس پیستون
Combustion System	direct injection	سیستم احتراق
Aspiration	Turbo, inter cool	سیستم تنفس
Rotation	Counter-clockwise	چرخش
Configuration	water-cooled	پیکر بندی
Air temperature	25 ° C	دمای هوا
Dimensions mm	1685×773×1065	ابعاد

ژنراتور

Manufacturer	Stamford	تولید کننده
Type	UCI274F	تیپ
Efficiency, %	91.7%	راندمان
Standby power at rated voltage, KVA	145	توان standby در ولتاژ نامی
Power factor	0.8	ضریب قدرت
Phase	3	فاز
Frequency, Hz	50	فرکانس
Voltage, V	380~440	ولتاژ
Stator windings	Double Layer Concentric	سیم پیچ استاتور
Voltage Regulation, %	$-0.5 < x < +0.5$	تنظیم ولتاژ
Rotor WDG. Resistance	1.52 اهم	مقاومت سیم پیچ (روتور)
Short circuit ratio	1/Xd	نسبت اتصال کوتاه
Insulation class	H	کلاس عایق
Protection class	IP23	کلاس حفاظتی

UCI274F

WINDING 311

CONTROL SYSTEM	SEPARATELY EXCITED BY P.M.G.		
A.V.R.	MX321	MX341	
VOLTAGE REGULATION	± 0.5 %	± 1.0 %	With 4% ENGINE GOVERNING
SUSTAINED SHORT CIRCUIT	REFER TO SHORT CIRCUIT DECREMENT CURVES (page 7)		

CONTROL SYSTEM	SELF EXCITED			
A.V.R.	SX460	SX440	SX421	
VOLTAGE REGULATION	± 1.5 %	± 1.0 %	± 0.5 %	With 4% ENGINE GOVERNING
SUSTAINED SHORT CIRCUIT	SERIES 4 CONTROL DOES NOT SUSTAIN A SHORT CIRCUIT CURRENT			

INSULATION SYSTEM	CLASS H							
PROTECTION	IP23							
RATED POWER FACTOR	0.8							
STATOR WINDING	DOUBLE LAYER CONCENTRIC							
WINDING PITCH	TWO THIRDS							
WINDING LEADS	12							
STATOR WDG. RESISTANCE	0.024 Ohms PER PHASE AT 22°C SERIES STAR CONNECTED							
ROTOR WDG. RESISTANCE	1.52 Ohms at 22°C							
R.F.I. SUPPRESSION	BS EN 61000-6-2 & BS EN 61000-6-4,VDE 0875G, VDE 0875N. refer to factory for others							
WAVEFORM DISTORTION	NO LOAD < 1.5% NON-DISTORTING BALANCED LINEAR LOAD < 5.0%							
MAXIMUM OVERSPEED	2250 Rev/Min							
BEARING DRIVE END	BALL. 6315-2RS (ISO)							
BEARING NON-DRIVE END	BALL. 6310-2RS (ISO)							
	1 BEARING				2 BEARING			
WEIGHT COMP. GENERATOR	530 kg				545 kg			
WEIGHT WOUND STATOR	200 kg				200 kg			
WEIGHT WOUND ROTOR	188.67 kg				177.71 kg			
WR² INERTIA	1.555 kgm²				1.5044 kgm²			
SHIPPING WEIGHTS in a crate	563 kg				577 kg			
PACKING CRATE SIZE	105 x 67 x 103(cm)				123 x 67 x 103(cm)			
	50 Hz				60 Hz			
TELEPHONE INTERFERENCE	THF<2%				TIF<50			
COOLING AIR	0.514 m³/sec 1090 cfm				0.617 m³/sec 1308 cfm			
VOLTAGE SERIES STAR	380/220	400/231	415/240	440/254	416/240	440/254	460/266	480/277
VOLTAGE PARALLEL STAR	190/110	200/115	208/120	220/127	208/120	220/127	230/133	240/138
VOLTAGE SERIES DELTA	220/110	230/115	240/120	254/127	240/120	254/127	266/133	277/138
KVA BASE RATING FOR REACTANCE VALUES	160	160	160	n/a	181.3	190	190	206.3
Xd DIR. AXIS SYNCHRONOUS	2.24	2.02	1.88	-	2.53	2.37	2.17	2.16
X'd DIR. AXIS TRANSIENT	0.19	0.17	0.16	-	0.21	0.20	0.18	0.18
X''d DIR. AXIS SUBTRANSIENT	0.13	0.12	0.11	-	0.14	0.13	0.12	0.12
Xq QUAD. AXIS REACTANCE	1.38	1.25	1.16	-	1.53	1.43	1.31	1.31
X''q QUAD. AXIS SUBTRANSIENT	0.17	0.15	0.14	-	0.20	0.19	0.17	0.17
XL LEAKAGE REACTANCE	0.07	0.06	0.06	-	0.09	0.08	0.08	0.08
X2 NEGATIVE SEQUENCE	0.14	0.13	0.12	-	0.16	0.15	0.14	0.14
X0ZERO SEQUENCE	0.08	0.08	0.07	-	0.10	0.09	0.09	0.09
REACTANCES ARE SATURATED		VALUES ARE PER UNIT AT RATING AND VOLTAGE INDICATED						
T'd TRANSIENT TIME CONST.	0.035 s							
T''d SUB-TRANSTIME CONST.	0.011 s							
T'do O.C. FIELD TIME CONST.	0.9 s							
Ta ARMATURE TIME CONST.	0.009 s							
SHORT CIRCUIT RATIO	1/Xd							

UCI274F

Winding 311 / 0.8 Power Factor




RATINGS

Class - Temp Rise		Cont. F - 105/40°C				Cont. H - 125/40°C				Standby - 150/40°C				Standby - 163/27°C			
50 Hz	Series Star (V)	380	400	415	440	380	400	415	440	380	400	415	440	380	400	415	440
	Parallel Star (V)	190	200	208	220	190	200	208	220	190	200	208	220	190	200	208	220
	Series Delta (V)	220	230	240	254	220	230	240	254	220	230	240	254	220	230	240	254
kVA		145.0	145.0	145.0	n/a	160.0	160.0	160.0	n/a	170.0	170.0	170.0	n/a	175.0	175.0	175.0	n/a
kW		116.0	116.0	116.0	n/a	128.0	128.0	128.0	n/a	136.0	136.0	136.0	n/a	140.0	140.0	140.0	n/a
Efficiency (%)		92.3	92.6	92.8	n/a	92.0	92.3	92.5	n/a	91.7	92.1	92.3	n/a	91.6	92.0	92.2	n/a
kW Input		125.7	125.3	125.0	n/a	139.1	138.7	138.4	n/a	148.3	147.7	147.3	n/a	152.8	152.2	151.8	n/a

60 Hz	Series Star (V)	416	440	460	480	416	440	460	480	416	440	460	480	416	440	460	480
	Parallel Star (V)	208	220	230	240	208	220	230	240	208	220	230	240	208	220	230	240
	Series Delta (V)	240	254	266	277	240	254	266	277	240	254	266	277	240	254	266	277
	kVA	162.5	172.5	172.5	187.5	181.3	190.0	190.0	206.3	187.5	200.0	200.0	212.5	192.5	206.3	206.3	218.8
	kW	130.0	138.0	138.0	150.0	145.0	152.0	152.0	165.0	150.0	160.0	160.0	170.0	154.0	165.0	165.0	175.0
	Efficiency (%)	92.5	92.7	92.9	92.9	92.1	92.4	92.7	92.7	92.0	92.2	92.5	92.6	91.9	92.1	92.4	92.5
	kW Input	140.5	148.9	148.5	161.5	157.5	164.5	164.0	178.0	163.0	173.5	173.0	183.6	167.6	179.2	178.6	189.2

DIMENSIONS



SINGLE BEARING ADAPTORS				
ADAPTOR	A	B	C	D
SAE 1	928,3	865,3	389,3	216,3
SAE 2	914	851	375	202
SAE 3	914	851	375	202

COUPLING DISCS	
DISC	AN
SAE 10	53,98
SAE 11,5	39,68
SAE 14	25,40



PO Box 17 • Barnack Road • Stamford • Lincolnshire • PE9 2NB

Tel: 00 44 (0)1780 484000 • Fax: 00 44 (0)1780 484100

Website: www.newage-avkseg.com