

Engine Specifications		
Brand		VOLVO PENTA
Model		TAD530GE
Engine Power Stand BY	(kWm / hp)	83/113
Revolution Per Minute	(r.p.m.)	1500
Total Displacement	(L)	4.76
Cylinders Orientation		4 SINGLE LINE
Bore x Stroke	(mm x mm)	108 x 130
Compression Orientation		18:1
Governor Type		MECHANICAL
Aspiration System		TURBO CAC
Injection		DIRECT
Cooling		WATER COOLED
Electrical System	(VDC)	12
Lub-Oil Capacity	(L)	13
Engine Coolant Capacity	(L)	19.7
Fuel Tank Capacity	(L)	200
Maximum Exhaust Temperature	(°C)	527
Maximum Exhaust Gas Flow	(m3/h)	894
Maximum Allowed Back Pressure	(kPa)	5
Cooling Air Flow	(m3/min)	120
Fuel Consumption 50 %	(L/h)	10
Fuel Consumption 75 %	(L/h)	15
Fuel Consumption 100 %	(L/h)	19


- Replacable cylinder jacket
- Dry type replacable oil filter
- Heat-resistant radiator for 50 °C

Alternator Specifications		
Output Voltage	(V)	400/230
Frequency	(Hz)	50
Stationary Voltage Regulation	(±)	1 %
Short Circuit Current		> 300 %
Insulation		H
Protection		IP 23
Efficiency	(%)	90.6
Overloading		110 % FOR 1 HOUR
Power Factor	(cos Phi)	0.8
Total Harmonic Distortion Rate		THF < 3 %
Connection Type		STAR
Number Of Pole		4
Number Of Bearing		SINGLE

- 4 Poles, Self-Excitation and Self-Cooled, Brushless, Synchronotype alternator
- Electronic type automatic voltage regulator (AVR)

Dimensions Without Canopy

Dimensions and Weight		
Length (L)	mm	2150
Height (H)	mm	1590
Width (W)	mm	1100
Wet weight	kg	1150
Fuel Tank Capacity	L	200



Dimensions With Canopy

Dimensions and Weight		
Length (L)	mm	2550
Height (H)	mm	1800
Width (W)	mm	1100
Wet weight	kg	1520
Fuel Tank Capacity	L	200



Control Panel Features

- Diesel and gas genset support
- 400Hz operation support
- 400 event logs, full snapshot
- All parameters front panel editable
- 3 level configuration password
- 128x64 graphical LCD display
- Downloadable language
- Waveform display of V & I
- Harmonic analysis of V & I
- Synchroscope & check synch
- Allows closed transfers
- 16Amp MCB & GCB outputs
- 8 configurable digital outputs
- Outputs expandable to 40
- 4 configurable analog inputs
- Both CANBUS-J1939 & MPU
- 3 configurable service alarms
- Multiple nominal conditions
- Multiple automatic exerciser
- Weekly operation schedule
- Dual mutual standby with equal aging of gensets
- Manual "speed fine adjust" on selected ECUs
- Automatic fuel pump control
- Disable protections feature
- Excess power protection
- Reverse power protection
- Overload IDMT protection
- Load shedding, dummy load
- Multiple load management
- Current unbalance protection
- Voltage unbalance protection
- Fuel filling & fuel theft alarms
- Battery back-up real time clock
- Idle speed control
- Battery charge0 run enabled
- Combat mode support
- Contactor & MCB drive
- 4 quadrant genset power counters
- Mains power counters
- Fuel filling counter
- Fuel consumption counter
- Modem & Ethernet diagnostics
- Configurable through USB, RS-485, Ethernet and GPRS
- Free configuration program
- Allows SMS controls
- Ready for central monitoring Ethernet and GPRS
- Mobile genset support
- Automatic GSM geo-location
- GPS connectivity (USB & RS232)
- Dynamic DNS support
- Easy USB firmware upgrade
- IP65 rating with standard gasket